


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47L 13/22	A1	(11) International Publication Number: WO 98/23200 (43) International Publication Date: 4 June 1998 (04.06.98)
--	-----------	---

(21) International Application Number: **PCT/US97/21561**(22) International Filing Date: **26 November 1997 (26.11.97)**(30) Priority Data:
08/756,774 **26 November 1996 (26.11.96)** **US**(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH
45202 (US).(72) Inventors: **PING, Vernon, Sanford**; 10044 Daly Road, Cincinnati, OH 45231 (US). **SCHENNUM, Steven, Michael**; 9853 Casey's Crossing, West Chester, OH 45069 (US). **DYE, Noelle, Marie**; 81 1/2 Warren Street, Charlestown, MA 02129 (US). **GUNDLACH, John, David**; 309 Dodge Road, Rowley, MA 01969 (US).(74) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).(81) Designated States: **AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).****Published***With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*(54) Title: **CLEANING IMPLEMENT HAVING A SPRAYER NOZZLE ATTACHED TO A CLEANING HEAD MEMBER****(57) Abstract**

A cleaning implement (1) having a liquid delivery system, includes a handle (2) with first and second ends, a cleaning head member (3) attached to the handle (7) at the first end, and a sprayer nozzle (4) preferably attached to the cleaning head member (3), independent of the handle (2), for providing increased directional control of the sprayer nozzle.

**BEST AVAILABLE COPY**

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

CLEANING IMPLEMENT HAVING A SPRAYER NOZZLE ATTACHED TO A CLEANING HEAD MEMBER

Field of the Invention

This invention relates to the field of cleaning implements, and more particularly, to a cleaning implement having a handle, a cleaning head member and a sprayer nozzle attached to the cleaning head member, independent of the handle, for providing increased control of the direction of the fluid dispensed from the sprayer nozzle.

Background of the Invention

Conventional straight handled cleaning implements, such as mops, are known and typically comprise a handle attached to a substantially flat cleaning head member by a universal joint. These devices are generally controlled by applying a force to the handle which results in the cleaning head member moving in the direction of the force. Cleaning implements which utilize a universal joint have increased maneuverability by rotating the shaft of the handle. In this way, the cleaning head member moves in a clockwise or counter-clockwise direction depending on the rotation of the handle.

In addition, cleaning implements are known which include a liquid delivery system to dispense cleaning fluid through a sprayer nozzle, in the vicinity of the cleaning head member. However, these cleaning implements typically utilize a sprayer nozzle attached to the handle of the cleaning implement and not directly to the cleaning head member. As a result, there is limited ability to control the direction of the sprayer nozzle, and consequently, an inability to control the direction of the fluid which is dispensed.

Unlike the cleaning head member, a sprayer nozzle mounted on the handle will not move in the direction of the cleaning head member, but will instead, only rotate with the handle's shaft. As a result, the sprayer nozzle cannot be controlled to the same degree as the cleaning head member. Therefore, the fluid dispensed by the sprayer nozzle will be directed away from the cleaning head member, and more importantly, away from the cleaning surface. In addition, the fluid dispensed in this manner could be dispensed on

objects and/or surfaces which are not intended to be cleaned. In this way, the cleaning fluid is wasted and, in some cases, may ruin items such as furniture.

Straight handled cleaning implements are also known which utilize a sprayer nozzle attached to the bottom of the cleaning surface. However, this is undesirable when using a cleaning fabric which is designed to wick the cleaning fluid from the cleaning surface as this type of system does not allow the cleaning fluid to contact the cleaning surface for a sufficient period of time to provide maximum cleaning.

Therefore, what is needed is a cleaning implement having a sprayer nozzle attached to the cleaning head member, independent of the handle, for providing increased directional control of the sprayer nozzle.

Summary of the Invention

Accordingly, it is an object of the present invention to provide an improved cleaning implement having a sprayer nozzle.

It is a further object of the present invention to provide a cleaning implement having a liquid delivery system, a handle with first and second ends, a cleaning head member preferably attached to the handle at the first end, and a sprayer nozzle attached to the cleaning head member, independent of the handle, for dispensing liquid from the liquid delivery system providing increased directional control of the sprayer nozzle.

Brief Description of the Drawing

FIG. 1 is a perspective view of the preferred cleaning implement according to the preferred embodiment of the present invention.

FIG. 2 is a top view of the preferred cleaning implement according to the preferred embodiment of the present invention.

Detailed Description of the Invention

Referring to FIGS. 1 and 2, the preferred cleaning implement 1 comprises a handle 2, a cleaning head member 3 and a sprayer nozzle 4, attached to the cleaning head member 3, independent of the handle 2, for providing increased directional control of the sprayer nozzle 4, and subsequently, the fluid dispensed from the sprayer nozzle 4. In this way, the quantity, trajectory, particle size, and fan angle of the liquid delivered from the sprayer nozzle 4 can be controlled, relative to the cleaning head member 3, for maximum cleaning results.

The cleaning head member 3 is preferably pivotally attached to the handle 2 at a first end by a universal joint 5 but may be attached in a variety of ways. The sprayer nozzle 4 is fed by a liquid delivery system 4a having a liquid filled canister 4b, both of which are

preferably attached to the handle 2. The preferred implement 1 also includes a cleaning fabric 6 removably attached to a substantially flat lower surface 7, preferably a foam bumper pad, of the head member 3. The cleaning fabric 6 is preferably attached using hook fasteners which are molded onto the surface 7. In addition, the preferred implement 1 includes an ergonomic grip 8 but may not utilize any grip without deviating from the intent of the invention.

The sprayer nozzle 4 is preferably attached to the upper surface 9 of the head member 3, adjacent the leading edge 10. In this way, the sprayer nozzle 4 moves in the direction of the head member 3 when the preferred implement is maneuvered. Specifically, the preferred implement 1 is maneuvered by rotating the handle 2 in a clockwise direction 11 or counter-clockwise direction 12. As a result, the rotational force will be translated, via the universal joint 5, to the head member 3 which will pivot correspondingly in the clockwise direction 11 or counter-clockwise direction 12, depending on the rotational direction of the handle 2.

Alternatively, the sprayer nozzle 4 may be attached to the lower section of the universal joint 5 or within the head member 3 without deviating from the intent of the invention. By attaching the sprayer nozzle 4 to the head member 3, or alternatively the lower section of the universal joint 5, the sprayer nozzle 4 follows the direction of the pivoting head member 3 and not the direction of the handle 2 as in the prior art. In this way, the preferred implement 1 enables delivery of the cleaning fluid in the direction of the head member 3, thereby providing optimum cleaning by focusing the cleaning fluid on the desired surface.

While the embodiment of the invention shown and described is fully capable of achieving the results desired, it is to be understood that this embodiment has been shown and described for purposes of illustration only and not for purposes of limitation. Other variations in the form and details that occur to those skilled in the art and which are within the spirit and scope of the invention are not specifically addressed. Therefore, the invention is limited only by the appended claims.

1. A cleaning implement having a liquid delivery system, characterized by:
a handle having first and second ends;
a cleaning head member attached to said first end of said handle; and
a sprayer nozzle for dispensing liquid from the liquid delivery system,
wherein said sprayer nozzle is attached to said cleaning head member, independent of said handle, for providing increased directional control of said sprayer nozzle.
2. A cleaning implement having a liquid delivery system, characterized by:
a handle having first and second ends;
a cleaning head member attached to said first end of said handle via a
universal joint; and
a sprayer nozzle for dispensing liquid from the liquid delivery system,
wherein said sprayer nozzle is attached to said universal joint, independent of said handle,
for providing increased directional control of said sprayer nozzle.
3. The cleaning implement according to any of the preceding claims,
further characterized by a cleaning fabric removably attached to said cleaning head
member.
4. The cleaning implement according to any of the preceding claims,
wherein said cleaning head member has a substantially flat surface.
5. The cleaning implement according to any of the preceding claims,
wherein said cleaning fabric is attached to said substantially flat surface.
6. The cleaning implement according to any of the preceding claims,
wherein said sprayer nozzle is attached on an upper surface of said cleaning head member,
opposite of said substantially flat surface.
7. The cleaning implement according to any of the preceding claims,
wherein said cleaning head member is pivotally attached to said handle.

8. The cleaning implement according to any of the preceding claims, wherein said cleaning head member is pivotally attached to said handle by a universal joint.

9. The cleaning implement according to any of the preceding claims, wherein said sprayer nozzle is attached within said cleaning head member.

10. The cleaning implement according to any of the preceding claims, further characterized by an ergonomic grip member attached to said second end of said handle.

11. The cleaning implement according to any of the preceding claims, wherein said sprayer nozzle has at least one of a fluidic oscillating spray, a fan angled spray and a uniform distribution.

12. The cleaning implement according to any of the preceding claims, wherein said sprayer nozzle produces an audible sound when dispensing the liquid.

1/2




Fig. 2




Fig. 1

BEST AVAILABLE COPY

2/2




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 4C

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/21561

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A47L13/22

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 018, no. 553 (C-1263), 21 October 1994 -& JP 06 197855 A (SHIMOMURA KOMUTEN:KK), 19 July 1994, see abstract; figures 1,5,6,11 ----	1,3-7,12
X	US 5 007 753 A (ENGLAND JR RAYMOND B) 16 April 1991 see abstract; figures 1,5,6 ----	1,12
A	FR 2 639 818 A (ROCHEX) 8 June 1990 see abstract; figures 1,3 ----	1-10,12
A	US 4 119 386 A (CUSHING ERNEST W) 10 October 1978 see column 3, line 64 - column 4, line 24; figures 1,2 -----	1-7,9,12

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 March 1998

Date of mailing of the international search report

01/04/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cabral Matos, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/21561

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5007753 A	16-04-91	NONE	
FR 2639818 A	08-06-90	DE 3940123 A	07-06-90
US 4119386 A	10-10-78	NONE	

THIS PAGE BLANK (USPTO)